EVOline® T-Dock





Member of




EVOline® T-Dock

The EVOline T-Dock is raised above the work surface by its solid stainless steel pillar. This gives clutter free space and creates a safe distance between power supply and potentially wet surfaces in the kitchen.

The power supply cable is routed through the stainled steel pillar which is also a high quality anti-theft device since it is firmly screwed beneath the surface.





Dimensions in inch

EVOline® T-Dock

Description	Picture	Specifications	Order Number
EVOline T-Dock Aluminium housing in stainless		Plastic end caps lacquered in black	1593 0220 5600
steel optics, ALANOX®. For surface thickness up to 50 mm. Two sockets, VDE-compliant, 0°, 16 A, contact-protected. Fixed supply cable with wire end ferrules, plug supplied unattached.	Etons,	Plastic end caps lacquered in stainless steel optics, ALANOX®	1593 0345 5600
Power supply cable entry through the stainless steel pillar.			
EVOline T-Dock mit USB Charger Aluminium housing in stainless steel optics, ALANOX [®] .		Plastic end caps lacquered in black	1593 0387 4600
For surface thickness up to 50 mm.	Bares	Plastic end caps lacquered	1593 0387 5600

in stainless steel optics,

ALANOX®

50 mm. One socket, VDE-compliant, 0°, 16 A, contact-protected. 1x USB-Charger Type A Output voltage: 5 V DC Rated output current: 1A

Fixed supply cable with wire end ferrules, plug supplied unattached. Power supply cable entry through the stainless steel pillar.

* The USB charging function cannot be guaranteed due to the multitude of manufacturers and devices on the market.

EVOline[®]

USA

Schulte Electro Systems Corp.

41W020 Seavey Road Sugar Grove, Il. 60554-9573

Telephone +1 (0) 630 / 409 9445 Telefax +1 (0) 630 / 406 0505

E-Mail info@evoline-usa.com Internet www.evoline-usa.com

Germany

Schulte Elektrotechnik GmbH & Co. KG

Juengerstraße 21 D-58515 Luedenscheid

Telephone	+49 (0) 23 51 / 94 81-0
Telefax	+49 (0) 23 51 / 4 26 58

E-Mail info@schulte.com Internet www.evoline.com

