



UL listed and tested to meet UL 1363 with 1 – 8 socket outlets. Electrical codes vary by location. Please check with your electrician to verify that this unit meets your local code before installing.

EVOline Dock sits above the desk allowing maximum workspace. Various fixing options are available like EVOline Quicklock, clamps, pillars, etc.

The configurable charging and data station can be equipped with the complete EVOline Modules range.





| Description | Picture | Specifications | Order Number |
|---|---------|--|----------------------------------|
| EVOline Dock 2x UL socket, NEMA 5-15, with tamper resistance, black, 1x USB-Charger 6 ft cord with UL plug. Cable lengths described from modu- | IR IR I | Aluminum profile silver anodized, silver endcaps Aluminum profile black anodized, black endcaps | 1593 0393 7300 1593 0393 7100 |
| le inside the profile to plug or socket on the end of the cable. | | Aluminum profile white powder coated, white endcaps | 1593 0393 7700 |
| Empty Housing EVOline Dock BLACK Aluminium housing | (Dove | Aluminum profile black anodized, black endcaps | 9330 1811 6600 |
| Empty Housing EVOline Dock SILVER Aluminium housing | | Aluminum profile silver anodized, black endcaps | 9330 1810 6600 |
| Empty Housing EVOline Dock STAINLESS Aluminium housing | | Aluminum profile ALANOX anodized, black endcaps | 9330 8450 6600 |
| Empty Housing EVOline Dock WHITE Aluminium housing | | Aluminum profile white powder coated, white endcaps | 9331 3530 6600 |







EVOline® Dock with QuickLock Pro Connector and WireLane Cable Management

EVOline[®] Accessories



EVOline[®] Accessoires

| Description | Picture | Specifications | Order Number |
|---|---------------|--------------------------|----------------|
| lounting Clamp | | Span width: | |
| 5 . | | 8 - 40 mm | 1599 0902 1200 |
| | - 37 | (5/16 - 1 37/64") | |
| wist-proof including non-slip | | 8 - 40 mm | 1599 0902 0500 |
| overing | | (5/16 - 1 37/64"), 2× | |
| Colour: black | | 40 - 75 mm | 1599 0902 1300 |
| or profiles: | | (1 37/64 - 2 61/64") | |
| ock, U-Dock, R-Dock | | 40 - 75 mm | 1599 0902 1000 |
| | | (1 37/64 - 2 61/64"), 2× | |
| founting Clamp | | Span width: | |
| | | 8 - 40 mm | 1599 0909 3300 |
| | Trans | (5/16 - 1 37/64") | |
| wist-proof including non-slip | | 8 - 40 mm | 1599 0909 5600 |
| overing | | (5/16 - 1 37/64"), 2× | |
| Colour: white | | 40 - 75 mm | 1599 0909 3900 |
| or profiles: | | (1 37/64 - 2 61/64") | |
| lock, U-Dock, R-Dock | | 40 - 75 mm | 1599 0909 5700 |
| | | (1 37/64 - 2 61/64"), 2× | |
| | | | |
| tainless Steel Mounting Clamp | | For Tabletops thickness | 1599 0909 1500 |
| wist-proof desk clamp for EVOline | | 45/64 - 63/64" | |
| rofiles, installed and secured with | | | |
| llen screws | | | |
| for profiles: | | | |
| lock, U-Dock, R-Dock | | | |
| | | | |
| | | | |
| lounting set | | | 1599 0903 8300 |
| or under cabinet installation | | | |
| anaista aftura EVOlizza Daaluk | | | |
| onsists of two EVOline Dock bra- kets with wood screws | | | |
| crew: 3,5 × 15 mm (1/8 x 19/32") | 1 1 1 1 1 1 1 | | |
| crew. 3,3 × 13 mm (1/6 × 19/32) | | | |
| | | | |
| | | | |
| | | | |
| lounting set | | | 1599 0903 8200 |
| or desk installation | | | |
| | | | |
| onsists of two EVOline Dock bra- | | | |
| kets with wing nut screws | 8 | | |
| crew: M4 x 40 mm (5/32 x 1 37/64") | | | |
| | | | |
| | | | |

EVOline[®] Accessoires

| Description | Picture | Specifications | Order Number |
|--|---------|---|----------------------------------|
| Angle Profile for fixing of EVOline V-Dock | | Length: 100 mm (3 15/16") Length: 60 mm (2 23/64") | |
| EVOline Quicklock Pro fixing system with a concealed cable channel and 2 fasteners, for surface thickness of 18 to 32 mm, installation without tools, fasteners with protective underlay for profiles: EVOline Dock, EVOline R-Dock | | Length: 100 mm (3 15/16") without bracket length: 150 mm (5 29/32") includes bracket for EVO- | 1599 0910 8500 1599 0910 8300 |
| | | line WireLane connection length: 200 mm (7 7/8") includes bracket for EVOline WireLane con- nection | 1599 0910 8400 |
| EVOline Rubber gasket fits under the collar of the EVOline Port. | | | 1599 0903 9100 |
| EVOline Laptop Secure Sturdy mounting lug for commercial laptop anti-theft devices. Such as Kensington Lock. | | Die-cast, silver-colored Length: 41 mm (1 39/64") Breite: 9 mm (23/64") Höhe: 22 mm (55/64") | 9331 3140 0000 |

EVOline[®] Made in Germany



Schulte Elektrotechnik GmbH & Co. KG

Jüngerstraße 21 D - 58515 Lüdenscheid Germany

| Telefon | +49 23 51 / 94 81 - 0 |
|----------|-----------------------|
| Fax | +49 23 51 / 4 26 58 |
| e-mail | info@schulte.com |
| Internet | www.evoline.com |

Schulte Electro Systems Corporation

41W020 Seavey Road Sugar Grove, IL 60554-9573 USA

phone +1 630-409-9445

e-mail sales@evoline-usa.com Internet www.evoline-usa.com



invented and made by schulte Schulte Elektrotechnik, Lüdenscheid, Germany

