

EVoline® R-Dock





UL listed and tested to meet UL 962A with 1 – 8 socket outlets.
Electrical codes vary by location. Please check with your electrician
to verify that this unit meets your local code before installing.





Contemporary and modern for all workspaces.

EVoline® R-Dock

EVoline R-Dock can be installed into any right-angled corner.

With its flat back and angled front fascia, it is comfortable to use. Freely configurable.



Description	Picture	Specifications	Order Number
<p>EVoline R-Dock</p> <p>2x UL socket, NEMA 5-15, with tamper resistance, 1x USB-Charger 6 ft cord with UL plug. Cable lengths described from modu- le inside the profile to plug or socket on the end of the cable.</p> 		Silver anodised	1598 0001 1900
<p>Empty Housing EVoline R-Dock</p> <p>Aluminium housing.</p>		Silver anodised	9331 0620 6600
<p>Empty Housing EVoline R-Dock</p> <p>Aluminium housing.</p>		White powder-coated	9331 4340 6600






1) Technical changes and printing errors reserved.








EVoline® R-Dock with Stainless Steel Mounting Clamp

EV0line® Accessories



Description	Picture	Specifications	Order Number
Mounting Clamp twist-proof including non-slip covering Colour: black for profiles: Dock, U-Dock, R-Dock		Span width: 8 - 40 mm (5/16 - 1 37/64") 8 - 40 mm (5/16 - 1 37/64"), 2× 40 - 75 mm (1 37/64 - 2 61/64") 40 - 75 mm (1 37/64 - 2 61/64"), 2×	1599 0902 1200 1599 0902 0500 1599 0902 1300 1599 0902 1000
Mounting Clamp twist-proof including non-slip covering Colour: white for profiles: Dock, U-Dock, R-Dock		Span width: 8 - 40 mm (5/16 - 1 37/64") 8 - 40 mm (5/16 - 1 37/64"), 2× 40 - 75 mm (1 37/64 - 2 61/64") 40 - 75 mm (1 37/64 - 2 61/64"), 2×	1599 0909 3300 1599 0909 5600 1599 0909 3900 1599 0909 5700
Stainless Steel Mounting Clamp twist-proof desk clamp for EVoline profiles, installed and secured with allen screws For profiles: Dock, U-Dock, R-Dock		For Tabletops thickness 45/64 – 63/64"	1599 0909 1500
Mounting set for under cabinet installation consists of two EVoline Dock brackets with wood screws screw: 3,5 × 15 mm (1/8 x 19/32")			1599 0903 8300
Mounting set for desk installation consists of two EVoline Dock brackets with wing nut screws screw: M4 x 40 mm (5/32 x 1 37/64")			1599 0903 8200

Description	Picture	Specifications	Order Number
Angle Profile for fixing of EVoline V-Dock		Length: 100 mm (3 15/16") Length: 60 mm (2 23/64")	1599 0908 4400 1599 0909 6400
EVoline Quicklock Pro fixing system with a concealed cable channel and 2 fasteners, for surface thickness of 18 to 32 mm, installation without tools, fasteners with protective underlay for profiles: EVoline Dock, EVoline R-Dock	 	Length: 100 mm (3 15/16") without bracket length: 150 mm (5 29/32") includes bracket for EVO-line WireLane connection length: 200 mm (7 7/8") includes bracket for EVoline WireLane connection	1599 0910 8500 1599 0910 8300 1599 0910 8400
EVoline Rubber gasket fits under the collar of the EVoline Port.			1599 0903 9100
EVoline Laptop Secure Sturdy mounting lug for commercial laptop anti-theft devices. Such as Kensington Lock.		Die-cast, silver-colored Length: 41 mm (1 39/64") Breite: 9 mm (23/64") Höhe: 22 mm (55/64")	9331 3140 0000

EVoline® Made in Germany



Schulte Elektrotechnik GmbH & Co. KG

Jüngerstraße 21
D - 58515 Lüdenscheid
Germany

Telefon +49 23 51 / 94 81 - 0
Fax +49 23 51 / 4 26 58
e-mail info@schulte.com
Internet www.evoline.com

Schulte Electro Systems Corporation

41W020 Seavey Road
Sugar Grove, IL 60554-9573
USA

phone +1 630-409-9445
e-mail sales@evoline-usa.com
Internet www.evoline-usa.com



invented and made by
Schulte Elektrotechnik,
Lüdenscheid, Germany

